MATERIAL	SAFETV	DATA	SHFFT

001172 / #341

NFPA RATING: Health	h = 0	Flammability =	0	Reactivity =	0
HMIS RATING: Healt	h = 0	Flammability =	0	Reactivity =	0

SECTION I -- IDENTITY AND MANUFACTURER'S INFORMATION (0617A)

Manufacturer's Name:	HILLYARD INDUSTRIES	Product Name:	SEAL 341
Address:	302 North Fourth Street	Date Prepared:	June 7, 1994
	St. Joseph, MO 64501	Prepared by:	Regulatory Affairs Department
Emergency Telephone	No.: (800)-424-9300 (Only in the even	nt of chemical eme	rgency involving a spill, leak, fire,

Emergency Telephone No.: (800)-424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals.) Other information calls: (816) 233-1321 (Ext. 2303)

SECTION II -- INGREDIENTS/IDENTITY INFORMATION

Components			ACGIH	OTHER LIMITS	
(Specific Chemical Identity:	CAS#	OSHA PEL	TLV	RECOMMENDED	%
Common Name(s)					
Zinc oxide ⁽¹⁾	1314-13-2	5 mg/M ³	5 mg/M^3	N/A	0.2-0.5
Water	7732-18-5	none	none	N/A	
Acrylic copolymer	unknown to	not	not	N/A	
	Hillyard	established	established		
Styrene acrylic emulsion	unknown to	not	not	N/A	000
	Hillyard	established	established		
Tributoxyethyl phosphate*	78-51-3	not	not	N/A	1-2.5
		established	established		
Diethylene glycol monoethyl ether*	111-90-0	not	not	N/A	1-2
		established	established		
Diethylene glycol mono methyl ether* ⁽²⁾	111-77-3	not	not	N/A	1-2
		established	established		

(1) Regulated by OSHA and the following states: FL., IL., LA., MA., NJ.

(2) Regulated by the following states: FL., PA., RI.

*This product contains the following chemicals subject to the reporting requirements of SARA Title III, Section 313, and 40 CFR Part 372: Tributoxyethyl phosphate, Diethylene glycol monoethyl ether and Diethylene glycol mono methyl ether.

SECTION III -- PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point: (739 mm Hg.) 198.26°F	Specific Gravity (H20 = 1): 25°C = 1.04 & 39°C = 1.03
Vapor Pressure (mm Hg.): 21.1	Percent Volatile by Volume (%): 77.8
Vapor Density (AIR = 1): 1.1	Evaporation Rate (ethyl ether = 1): slower than 1
Solubility in Water: appreciable	Appearance and Odor: milky emulsion: non-objectionable odor

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flash point: none (Tag Closed Cup)

Extinguishing Media: N/A

Flammable Limits: LEL = N/A UEL = N/A

Special Fire Fighting Procedures: None

Unusual Fire and Explosion Hazards: Material may spatter if temperature exceeds boiling point. Polymer film can burn.

SECTION V -- PHYSICAL HAZARDS

Stability: Stable Conditions to Avoid: N/A

Incompatibility (Materials to Avoid): None known

Hazardous Decomposition Products or Byproducts: Thermal decomposition may yield acrylic monomers (avoid temperatures above 177°C/350°F). Thermal decomposition is dependent on time and temperature. Hazardous Polymerization: Will not occur Conditions to Avoid: N/A

SECTION VI HEALTH	HAZARD DATA	
Routes of entry:	Inhalation? N/A	
HEALTH HAZARDS (1. A	Acute and 2. Chronic)	

Skin? N/A Ingestion? N/A

MAY 3 0 2

2. None known.

1. Mild eye irritation.

01,02,03,04,05,06,07,08,09,10

page 2 of #341 - Seal 341

SECTION VI -- HEALTH HAZARD DATA cont.

Chemical listed as Carcinogen or Potential Carcinogen:

National Toxicology Program = No I.A.R.C. Monographs = No OSHA = No This product has no carcinogens listed by IARC, NTP, NIOSH, or ACGIH as of this date, greater than or equal to 0.1%.

Signs and Symptoms of Exposure: None known.

Medical Conditions Generally Aggravated by Exposure: None known.

Emergency and First Aid Procedures: If splashed into eyes flush with water for 15 minutes; if irritation persists get medical attention.

SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Pick up with mop or wet vac and wash away with water. Ventilate area of spill or leak. Transfer liquids and diking material to separate suitable containers for recovery or disposal. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

Waste Disposal Method: Spills should be picked up with wet vac or absorbent material. Dispose of liquid per federal, state and local regulations. Waste from normal product use may be sewered to a public owned treatment works (POTW) in compliance with applicable federal, state and local requirements.

Precautions To Be Taken In Handling And Storing: Freezing of product may rupture container. Product shelf life is best retained by storage at 45-100°F temperatures.

Other Precautions: Inhalation exposure to spray mist should be maintained at less than 10 mg/M^3 per eight hour exposure (TWA limit established for nuisance dust).

SECTION VIII -- CONTROL MEASURES

Respiratory Protection (Specify Type): When airborne exposure guidelines and/or comfort levels may be exceeded, use an approved air-purifying respirator.

Ventilation:

Local Exhaust =Not requiredMechanical (General) =SuggestedSpecial =N/AOther =N/AProtective Gloves:None required for brief contactEyeChemical goggles (contact may cause pain, though it is
unlikely to cause injury).

Other Protective Clothing or Equipment: Use good personal hygiene procedures. Work / Hygienic Practices: Do not take internally; wash contaminated clothing before reuse.

SECTION IX - TRANSPORTATION INFORMATION

Applicable regulations: 49 CFR = <u>no</u>; IMCO = <u>no</u>; IATA = <u>no</u>. Proper shipping name: <u>Liquid Floor Wax & Polish</u> UN No.: <u>not applicable</u>; Limited Qty.: <u>not applicable</u>; Hazard Class: <u>not applicable</u>. Labels required: <u>not required</u> DOT Exception: <u>not applicable</u> EPA Hazardous waste number / code: <u>not listed</u> Hazardous waste characteristics: Ignitability = <u>not applicable</u>; Corrosivity = <u>not applicable</u>; Reactivity = <u>not applicable</u>.

DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.

The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate.

THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.