



SAFETY DATA SHEET

Revision Date 24-Feb-2020

Version 7

1. IDENTIFICATION

Product identifier

Product Name 771 NICKEL ANTI-SEIZE LUBRICANT 8OZ BT

Other means of identification

Product Code 77124

Recommended use of the chemical and restrictions on use

Recommended Use Lubricant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address: mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

Emergency Overview

Signal word

Danger

May cause an allergic skin reaction
May cause cancer
Causes damage to organs through prolonged or repeated exposure



Appearance Silver

Physical state Paste Liquid

Odor Petroleum

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see .? on this label)

IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Toxic to aquatic life with long lasting effects.

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC	64741-96-4	50-75
GRAPHITE	7782-42-5	10 - 30
NICKEL	7440-02-0	5 - 10
ALUMINIUM POWDER	7429-90-5	1 - 5

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN: Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Use dry chemical, Foam

Unsuitable extinguishing media

Water

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.

Environmental precautions

Environmental precautions See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth or other non-combustible absorbent material. Take up mechanically, placing in appropriate

containers for disposal. Clean contaminated surface thoroughly.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Store locked up.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
GRAPHITE 7782-42-5	TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ natural respirable dust
NICKEL 7440-02-0	TWA: 1.5 mg/m ³ inhalable particulate matter	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 10 mg/m ³ IDLH: 10 mg/m ³ Ni TWA: 0.015 mg/m ³ TWA: 0.015 mg/m ³ except Nickel carbonyl Ni
ALUMINIUM POWDER 7429-90-5	TWA: 1 mg/m ³ respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 5 mg/m ³ Al

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles).
- Skin and body protection** Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
- Respiratory protection** Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Paste Liquid
Appearance	Silver
Odor	Petroleum
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	
Flash point	> 204 °C / > 399 °F	
Evaporation rate	< 1	Butyl acetate = 1
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	1.12	
Water solubility	Negligible	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
 Other Information		
Softening point	No information available	
Molecular weight	No information available	
Density	No information available	
Bulk density	No information available	
SADT (self-accelerating decomposition temperature)	No information available	

10. STABILITY AND REACTIVITY

Reactivity
No information available

Chemical stability
Stable under normal conditions

Possibility of Hazardous Reactions
None under normal processing.

Hazardous polymerization
Hazardous polymerization does not occur.

Conditions to avoid
Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides
Metal oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC 64741-96-4	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
GRAPHITE 7782-42-5	-	-	> 2000 mg/m ³ (Rat) 4 h
NICKEL 7440-02-0	> 9000 mg/kg (Rat)	-	> 10.2 mg/L (Rat) 1 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC 64741-96-4	A2	Group 1	Known	X
NICKEL 7440-02-0	-	Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
 IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
 NTP (National Toxicology Program)
Known - Known Carcinogen
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Target Organ Effects Central Vascular System (CVS), Nasal Cavities, Respiratory system, Skin, Eyes, Lungs.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5515 mg/kg
ATEmix (dermal) 5960 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

17 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

- Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated packaging** Do not reuse container.
- US EPA Waste Number** Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
NICKEL 7440-02-0	Toxic powder Ignitable powder
ALUMINIUM POWDER 7429-90-5	Ignitable powder

14. TRANSPORT INFORMATION

DOT

Proper shipping name Not regulated

IATA

Proper shipping name Not regulated

IMDG

Proper shipping name Not regulated

15. REGULATORY INFORMATION

International Inventories

- TSCA** Complies
- DSL/NDSL** Complies
- EINECS/ELINCS** Complies
- ENCS** Not determined
- IECSC** Complies

KECL Complies
PICCS Complies
AICS Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
NICKEL - 7440-02-0	0.1
ALUMINIUM POWDER - 7429-90-5	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
 Chronic Health Hazard No
 Fire hazard No
 Sudden release of pressure hazard No
 Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NICKEL 7440-02-0	-	X	X	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
NICKEL 7440-02-0	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
NICKEL 7440-02-0	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
GRAPHITE 7782-42-5	X	X	X
NICKEL 7440-02-0	X	X	X
ALUMINIUM POWDER 7429-90-5	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 1	Instability 0	-
<u>HMIS</u>	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Revision Date 24-Feb-2020

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet