Polyblend Non-Sanded Grout

1
0
0

1. Product And Company Identification

<u>Supplier</u>

CUSTOM BUILDING PRODUCTS 10400 Pioneer Blvd., Unit #3

Santa Fe Springs, CA 90670 UNITED STATES

Company Contact: GEORGE MARCINA Telephone Number: (562) 968-2980 Ext 103

FAX Number: (562) 903-2697 **E-Mail:** georgem@cbpmail.net

Web Site: www.custombuildingproducts.com

Supplier Emergency Contacts & Phone Number

GEORGE MARCINA: (562) 968-2980

Manufacturer

CUSTOM BUILDING PRODUCTS 10400 Pioneer Blvd., Unit #3

Santa Fe Springs, CA 90670 UNITED STATES

Company Contact: GEORGE MARCINA Telephone Number: (562) 968-2980 Ext 103

FAX Number: (562) 903-2697 **E-Mail:** georgem@cbpmail.net

Web Site: www.custombuildingproducts.com

Manufacturer Emergency Contacts & Phone Number

GEORGE MARCINA: (562) 968-2980

Issue Date: 01/30/2007

Product Name: Polyblend Non-Sanded Grout

Chemical Name: Grouts
CAS Number: Not Established
Chemical Formula: Mixture

MSDS Number: 818 Product Code: 7100

2. Composition/Information On Ingredients

	Ingredient Name	CAS Number		Percent Of Total Weight	
Calcium Sulfate		7778-18-9		1 - 5	
Iron Oxide Pigments		1317-61-9		0 - 5	
TitaniumDioxide		13463-67-7		1 - 5	
Calcium Carbonate		1317-65-3		30 - 40	
Portland Cement Portland Cement		65997-15-1		40 - 50	

3. Hazards Identification

Primary Routes(s) Of Entry

Inhalation, Skin Contact, Eye Contact, Ingestion

Eve Hazards

Irritant, severe eye irritation. May cause eye injury. Effects may be delayed.

Skin Hazards

Contains Portland cement and exposure to dry Portland cement may cause drying of skin with consequent mild irritation. Prolonged contact with wet Portland cement may cause severe, potentially irreversible damage to the skin in the form of chemical (caustic) burns.

Polyblend Non-Sanded Grout

3. Hazards Identification - Continued

Ingestion Hazards

Ingestion is not known to be harmful, however the product contains Portland cement which is caustic to mucus tissue and should not be consumed.

Inhalation Hazards

Causes respiratory tract irritation. May cause nose, throat, and lung irritation. May cause delayed lung injury.

Chronic/Carcinogenicity Effects

MAY CONTAIN TRACES OF SILICA SAND, KNOWN HUMAN CARCINOGEN. MAY CONTAIN OTHER CHEMICALS ON CA PROPOSITION 65 LIST.

4. First Aid Measures

Eve

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

DO NOT INDUCE VOMITING. If victim is fully conscious, give one or two cups of water or milk to drink. Get medical attention immediately.

Inhalation

If inhaled, remove to fresh air. Consult a physician immediately if irritation persists. Do not give an unconscious person anything to drink.

5. Fire Fighting Measures

Flash Point: N/A °F Flash Point Method: N/A Lower Explosive Limit: N/A Upper Explosive Limit: N/A

6. Accidental Release Measures

Avoid generating dust. Sweep up and remove immediately. Use appropriate personal protective equipment (PPE). OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS REGARDING NOTIFICATIONS OF ACCIDENTAL RELEASES.

7. Handling And Storage

Handling And Storage Precautions

Use only with adequate ventilation.

Handling Precautions

Avoid creating dust. Avoid breathing dust. Avoid contact with skin and clothing. Avoid contact with eyes.

Storage Precautions

Keep dry until ready to use.

Work/Hygienic Practices

Use good personal hygiene. Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

No Data Available...

Polyblend Non-Sanded Grout

8. Exposure Controls/Personal Protection - Continued

Engineering Controls

Use with adequate ventilation.

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

If hands or feet will be exposed, wear impervious gloves and/or boots.

Respiratory Protection

In case of inadequate ventilation and when exposed to dust above the recommended limits, wear a suitable NIOSH-approved respirator.

Ingredient(s) - Exposure Limits

Calcium Sulfate

TLV = 10 mg/m3

PEL = 15 mg/m3 (total)

PEL = 5 mg/m3 (respirable)

Titanium Dioxide

ACGIH TLV-TWA 10 mg/m3

OSHA PEL-TWA 15 mg/m3

Calcium Carbonate

OSHA - PEL - TWA - 15mg/m3

Niosh - REL 10 mg/m3

ACGIH- TLV - 10 mg/m3

OSHA - PEL - TWA - 5 mg/m3

Portland Cement

OSHA - PEL - 5mg/m3

OSHA - PEL - TWA - 50mppcf

ACGIH - TLV - 10mg/m3

9. Physical And Chemical Properties

<u>Appearance</u>

Free flowing colored powder.

Chemical Type: Mixture Physical State: Solid Melting Point: NA °F Boiling Point: N/A °F Specific Gravity: 2.7 Vapor Density: N/A Solubility: MINIMAL Evaporation Rate: N/A

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR.

Conditions To Avoid (Stability)

Avoid unintentional contact with water.

Incompatible Materials

Contains Portland cement which, when wet, is highly alkali. As a result, it is incompatible with acids, ammonium salts, aluminum and other alkali and alkaline earth metals.

Polyblend Non-Sanded Grout

11. Toxicological Information

Chronic/Carcinogenicity

MAY CONTAIN TRACES OF SILICA SAND, KNOWN HUMAN CARCINOGEN. MAY CONTAIN OTHER CHEMICALS ON CA PROPOSITION 65 LIST.

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

RCRA Information

Not considered RCRA Hazardous Waste.

14. Transport Information

DOT Shipping Label

NOT REGULATED

15. Regulatory Information

SARA Section 313 Notification

This product does not contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Ingredient(s) - State Regulations

Titanium Dioxide

New Jersey - Workplace Hazard Pennsylvania - Workplace Hazard New York City - Hazardous Substance

Calcium Carbonate

Pennsylvania - Workplace Hazard

Portland Cement

New Jersey - Workplace Hazard Pennsylvania - Workplace Hazard

16. Other Information

HMIS Rating

Health: 1 Fire: 0 Reactivity: 0

Personal Protection: E

Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA
MSDS Preparer Phone Number: (562) 968-2980 ext 103

This MSDS Supersedes A Previous MSDS Dated: 11/03/2006

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Polyblend Non-Sanded Grout

Disclaimer - Continued

CUSTOM BUILDING PRODUCTS

Printed Using MSDS Generator™ 2000