

MATERIAL SAFETY DATA SHEET



THE SHERWIN - WILLIAMS CO.
101 PROSPECT AVE. N.W.
CLEVELAND, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917
INFORMATION TELEPHONE NO.
(216) 566-2902

DATE OF PREPARATION
1 - MAR - 91

©1991, The Sherwin-Williams Co.

Alkyd Gloss & Specialty Finishes

A/3

						SWP [®] Exterior Gloss	ProMar [®] 200 Interior Gloss	ProMar [®] Gloss Barn Paint	ProMar [®] High Gloss SW 350	Masonry Conditioner	Polyurethane Floor Enamel	ProMar [®] Bronzotone Enamel	Controls Rust Enamel
						A2 B 18 Tricorn Black A2 G 40 Base C A2 R 33 Burgundy Base A2 R 36 Base D A2 W 28 White A2 W 32 Base A A2 W 524 Perma White A2 W 528 Tinting White A2 Y 30 Base B A2 Y 584 Yellow Corn	B35 W 201 Base X	B46 R A5 Red B46 W A35 White	B47 W 101 Pure White B47 W 104 Antique White	A5 V 2 Clear	A33 A 34 Light Grey A33 A 37 Medium Gray A33 A 46 Dark Gray A33 G 110 Evergreen A33 N 85 Walnut A33 R 65 The Red A33 W 62 White	B39 T 104 Base B39 N 1	K8 B 3 Gloss Black K8 B 14 Flat Black K8 E 8 Gloss Orange K8 G 8 Gloss Green K8 L 8 Gloss Blue K8 N 8 Gloss Brown K8 W 10 Gloss White K8 W 15 Flat White K8 Y 14 Gloss Yellow
SECTION II		ACGIH TLV	OSHA PEL <STEL>	UNITS	V.P.								
CAS No.	HAZARDOUS INGREDIENT (percent by weight)												
107-21-1	Ethylene Glycol.	C 50	C 50	PPM	0.1	<5% may be added in tinting							
64742-47-8 64742-88-7	Mineral Spirits. Mineral Spirits, 140-flash	100	100	PPM	2.0 0.5	29 - 42	42	34 - 37	34	53	44 - 46	33 - 34	32-46
64742-48-9	V. M. & P. Naphtha	300	300 <400>	PPM	12.0				4				
14808-80-7	Quartz	0.1	0.1	Mg/M3	as Resp. Dust	3 - 12						29 - 37	
14807-98-6	Talc	2	2	Mg/M3	as Resp. Dust			18 - 19				4 (In N1 only)	26 (In Flats only)
471-34-1	Calcium Carbonate	10	15(5)	Mg/M3	as Dust (Resp. Fraction)						2 - 10		
13483-87-7	Titanium Dioxide.	10	10(5)	Mg/M3	as Dust (Resp. Fraction)	0 - 21	24	15 (In WA35 only)	22 - 24		0 - 17	2 (In N1 only)	0 - 29
1333-86-4	Carbon Black	3.5	3.5	Mg/M3	as Resp. Dust	3 (In B18 only)							3 (In Blacks only)
1308-38-9	Chromium Oxide	0.50	0.50	Mg/M3							7 (In G110 only)		
8007-18-9	Nickel Antimony Titanate	0.5	0.5	Mg/M3		8 (in Y564 only)							
Volatile Organic Compounds (VOC) lb./gal.						2.89 - 3.52	3.79	3.40 - 3.42	3.51 - 3.55	3.89	3.92 - 3.94	3.39 - 3.40	3.20 - 3.89

Alkyd Finishes

Alkyd Finishes

A

Section III — PHYSICAL DATA

PRODUCT WEIGHT	- 8-13 lb./gal.	EVAPORATION RATE	- Slower than Ether
SPECIFIC GRAVITY	- 0.92-1.54	VAPOR DENSITY	- Heavier than Air
BOILING RANGE	- 300-448 F	MELTING POINT	- N.A.
VOLATILE VOLUME	- 32-65 %	SOLUBILITY IN WATER	- N.A.

Section IV — FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION FLASH POINT 102-105 F PMCC LEL 0.9 UEL 6.0
Combustible, Flash above 99 and below 200 F

EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS
Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES
Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V — HEALTH HAZARD DATA

ROUTES OF EXPOSURE
Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards
EFFECTS OF OVEREXPOSURE
Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE
Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.
Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
Contact with Chrome compounds (in A33G110 only) may cause allergic reactions in sensitized individuals.

EMERGENCY AND FIRST AID PROCEDURES
If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
If on SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.
If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED: Get medical attention.

CHRONIC Health Hazards
Crystalline Silica (Quartz, Cristobalite) is listed by IARC. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.
Chromium III (in A33G110 only) is considered the active species in cancer induction, but Chromium III compounds do not cross the cell wall. However, there is some evidence that Chromium III compounds of respirable particle size may be taken up by the cells in the lung.
Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.
Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, and urinary systems.
Rats exposed to titanium dioxide dust at 250 mg./m³ developed lung cancer, however, such exposure levels are not attainable in the workplace.
Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section VI — REACTIVITY DATA

STABILITY - Stable
INCOMPATIBILITY
None known.

HAZARDOUS DECOMPOSITION PRODUCTS
By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will Not Occur

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD
Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Waste containing Chromium Oxide (A33G110) must also be tested for extractability.
Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII — PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE
Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m³ (total dust), OSHA PEL 15 mg./m³ (total dust), 5 mg./m³ (respirable fraction).

VENTILATION
Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION
If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.
When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.


PROTECTIVE GLOVES
Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION
Wear safety spectacles with unperforated sideshields.

Section IX — PRECAUTIONS

DEL STORAGE CATEGORY - 2
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Contents are COMBUSTIBLE. Keep away from heat and open flame.
Consult NFPA Code. Use approved Bonding and Grounding procedures.
Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS
Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.



This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.
The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.