# CYCLO® SILICONE SPRAY



Version Revision Date: SDS Number: Date of last issue: 03/29/2023 09/29/2023 60000001129 Date of first issue: 08/23/2017 2.3

#### **SECTION 1. IDENTIFICATION**

CYCLO SILICN SPRAY AERO 12/10 OZ Product name

Product code C33V

Manufacturer or supplier's details

Company name of supplier Niteo Products, LLC

Address Dallas TX 75225

**Email Address** EHS@niteoproducts.com

Telephone 1-844-696-4836

Emergency telephone num-

ber

: 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use Lubricant

Restrictions on use Use only outdoors or in a well-ventilated area.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols Category 1

Skin irritation Category 2

Eye irritation Category 2B

Aspiration hazard Category 1

**GHS** label elements

Hazard pictograms







Signal word Danger

Hazard statements Extremely flammable aerosol.

May be fatal if swallowed and enters airways.

Causes skin and eye irritation.

Precautionary statements Prevention:

# CYCLO® SILICONE SPRAY



Version Revision Date: SDS Number: Date of last issue: 03/29/2023 2.3 09/29/2023 600000001129 Date of first issue: 08/23/2017

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Wash skin thoroughly after handling.

Wear protective gloves.

#### Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

## Storage:

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

# **Hazardous components**

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

| Distillates (petroleum) | 64742-47-8 | >= 30 - < 50 |
|-------------------------|------------|--------------|
| Propane                 | 74-98-6    | >= 30 - < 50 |
| Naphtha (petroleum)     | 64742-49-0 | >= 20 - < 30 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get med-

# CYCLO® SILICONE SPRAY



Version Revision Date: SDS Number: Date of last issue: 03/29/2023 2.3 09/29/2023 600000001129 Date of first issue: 08/23/2017

ical attention.

Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If swallowed : Obtain medical attention.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes skin and eye irritation.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

Carbon oxides

Silicon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment. Remove all sources of ignition.

Ensure adequate ventilation.

Avoid breathing dust.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

# CYCLO® SILICONE SPRAY



Version Revision Date: SDS Number: Date of last issue: 03/29/2023 2.3 09/29/2023 600000001129 Date of first issue: 08/23/2017

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Use only explosion-proof equipment.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Take precautionary measures against static discharges. Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Observe label precautions.

No smoking.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

| Components              | CAS-No.    | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis    |
|-------------------------|------------|-------------------------------------|--|----------|
| Distillates (petroleum) | 64742-47-8 | TWA (Mist)                          | 5 mg/m3  | OSHA Z-1 |
|                         |            | TWA                                 | 200 mg/m3<br>(total hydrocarbon<br>vapor)      | ACGIH    |





Version **Revision Date:** SDS Number: Date of last issue: 03/29/2023 09/29/2023 60000001129 Date of first issue: 08/23/2017 2.3

|                     |            | TWA (Mist) | 5 mg/m3                  | OSHA P0   |
|---------------------|------------|------------|--------------------------|-----------|
|                     |            | TWA (Mist) | 5 mg/m3                  | NIOSH REL |
|                     |            | ST (Mist)  | 10 mg/m3                 | NIOSH REL |
| Propane             | 74-98-6    | TWA        | 1,000 ppm<br>1,800 mg/m3 | NIOSH REL |
|                     |            | TWA        | 1,000 ppm<br>1,800 mg/m3 | OSHA Z-1  |
|                     |            | TWA        | 1,000 ppm<br>1,800 mg/m3 | OSHA P0   |
| Naphtha (petroleum) | 64742-49-0 | TWA        | 500 ppm<br>2,000 mg/m3   | OSHA Z-1  |
|                     |            | TWA        | 400 ppm<br>1,600 mg/m3   | OSHA P0   |

**Engineering measures** Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

# Personal protective equipment

Hand protection

Remarks Wear resistant gloves (consult your safety equipment suppli-

> er). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Not required under normal conditions of use. Wear splash-Eye protection

proof safety goggles if material could be misted or splashed

into eyes.

Choose body protection according to the amount and con-Skin and body protection

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Flame-resistant clothing

Safety shoes

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not smoke. When using do not eat or drink.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance aerosol

No data available Colour

Odour No data available

Odour Threshold No data available

pΗ No data available

Melting point/range No data available





Version Revision Date: SDS Number: Date of last issue: 03/29/2023 2.3 09/29/2023 600000001129 Date of first issue: 08/23/2017

Boiling point/boiling range : -42.1 °C

Value for Component

Flash point : -104.45 °C

Method: closed cup Value for Component

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

9.5 %(V)

Lower explosion limit / Lower

flammability limit

0.7 %(V)

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.766 g/cm3

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Molecular weight : No data available

VOC % By Weight : 59.75 %

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity: No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition : Silicon oxides

# **CYCLO® SILICONE SPRAY**



Version Revision Date: SDS Number: Date of last issue: 03/29/2023 2.3 09/29/2023 600000001129 Date of first issue: 08/23/2017

products Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion

# **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

**Components:** 

Distillates (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.52 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

# Skin corrosion/irritation

Causes skin irritation.

# **Components:**

### Distillates (petroleum):

Assessment: Irritating to skin. Result: Irritating to skin.

# Naphtha (petroleum):

Result: Possibly irritating to skin

# Serious eye damage/eye irritation

Causes eye irritation.

# **Product:**

Remarks: Unlikely to cause eye irritation or injury.

# **CYCLO® SILICONE SPRAY**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/29/2023

 2.3
 09/29/2023
 600000001129
 Date of first issue: 08/23/2017

### **Components:**

**Distillates (petroleum):**Result: Mild eye irritation

Naphtha (petroleum):

Result: Possibly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

**Components:** 

Propane:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

May be fatal if swallowed and enters airways.

# CYCLO® SILICONE SPRAY



Version **Revision Date:** SDS Number: Date of last issue: 03/29/2023 09/29/2023 60000001129 Date of first issue: 08/23/2017 2.3

# **Components:**

## Naphtha (petroleum):

May be fatal if swallowed and enters airways.

#### **Further information**

**Product:** 

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Toxicity** 

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues Dispose of in accordance with all applicable local, state and

federal regulations.

Empty remaining contents. Contaminated packaging

> Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14. TRANSPORT INFORMATION**

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# International Regulations

**IATA-DGR** 

UN/ID No. UN 1950

Proper shipping name Aerosols, flammable

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 Packing instruction (cargo 203

aircraft)

Packing instruction 203

(passenger aircraft)

**IMDG-Code** 

UN number UN 1950 Proper shipping name **AEROSOLS** 

Class 2.1

Packing group Not assigned by regulation





Version Revision Date: SDS Number: Date of last issue: 03/29/2023 2.3 09/29/2023 600000001129 Date of first issue: 08/23/2017

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**National Regulations** 

**49 CFR** 

UN/ID/NA number : UN 1950 Proper shipping name : Aerosols

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 ERG Code : 126 Marine pollutant : no

#### **SECTION 15. REGULATORY INFORMATION**

# **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Aspiration hazard

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.





Version 2.3

Revision Date: 09/29/2023


SDS Number: 60000001129

Date of last issue: 03/29/2023 Date of first issue: 08/23/2017

### **SECTION 16. OTHER INFORMATION**

### **Further information**

#### NFPA:



Special hazard

Revision Date : 09/29/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN