MATERIAL SAFETY DATA SHEET

FLOOR PATCH & LEVEL Page: 1

PRODUCT NAME: FLOOR PATCH & LEVEL HMIS CODES: H F R P

PROCUCT CODE: 2708-2709 0 0 0 0

======= SECTION I - MANUFACTURER IDENTIFICATION ===========

MANUFACTURER'S NAME: JASCO Chemical Corp.

ADDRESS: 1008 N. Fuller St.

Santa Ana, CA. 92701

====== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ==========

VAPOR PRESSURE WEIGHT

REPORTABLE COMPONENTS

CAS NUMBER

mm Hg @ TEMP

PERCENT

67-56-1

97.68

OSHA PEL: 200 PPM, ACGIH TLV: 200 PPM, OTHER: POISONOUS

*** No toxic chemical (s) subject to the reporting requirements of section 313 of Title III of 40 CFR 372 are present. *** CONTAINS SILICA SAND CAS NO 01-4808-60-7

========= SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ===============

BOILING RANGE: N/A **SPECIFIC GRAVITY (H2O=1):** 1.98 **VAPOR DENSITY:** UNKNOWN **EVAPORATION RATE:** UNKNOWN

COATING V.O.C.: 32.4 g/L

METHYL ALCOHOL; CARBINOL; COLONIAL SPIRIT

SOLUBILITY IN WATER: WATER RINSABLE **APPEARANCE AND ODOR:** SANDY PASTE

FLASH POINT: OVER 200 DEG. F METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 7.3 UPPER: 36

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

PRODUCT WILL NOT BURN UNTIL WATER CONTENT HAS EVAPORATED.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DECOMPOSITION BY-PRODUCTS MAY BE TOXIC. FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING EQUIPMENT.

STABILITY: STABLE CONDITIONS TO AVOID

KEEP FROM FREEZING. CLOSE CONTAINER AFTER USE.

INCOMPATIBILITY (MATERIALS TO AVOID)

ACIDS, HYDROFLORIC ACID, POWERFUL OXIDIZING AGENTS.

MATERIAL SAFETY DATA SHEET

Page:

FLOOR PATCH & LEVEL

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE, NITRIC OXIDE TRACES.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EXCESSIVE VAPOR CONCENTRATIONS IN CONFINED AREAS WITH POOR VENTILATION MAY CAUSE IRRITATION TO NOSE AND THROAT.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MAY CAUSE SKIN AND EYE IRRITATION.

SKIN ABSORPRTION HEALTH RISKS AND SYMPTONS OF EXPOSURE

LONG TERM EXPOSURE MAY RESULT IN DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

PRODUCT CAN CAUSE SEVERE ABDOMINAL PAINS, DISTRESS AND NAUSEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PRODUCT IS NOT CONSIDERED TOXIC. NO CHRONIC HEALTH EFFECTS ARE KNOWN AT PRESENT. THE SILICA SAND IN THE PRODUCT DOES NOT PRESENT A DUST OR INHALATION HAZARD BECAUSE IT IS HELD WITHIN THE EMULSION BASE. IT MAY HOWEVER PRESENT AN ABRASION HAZARD TO SENSITIVE INDIVIDUALS.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

PRODUCT CONTAINS SILICA SAND WHICH, IN CRYSTALINE FORM, HAS BEEN LABELED A LEVEL 2A POSSIBLE CARCINOGEN BY ARAC

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

PRE-EXISTING SKIN DISORDERS MAY BE AGGRAVATED BY THIS PRODUCT.

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: FLUSH EYES WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN CONTACT: WASH EFFECTED AREAS WITH MILD SOAP AND WATER. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. INGESTION: GIVE 3 TO 4 GLASSES OF WATER. INDUCE VOMITING (IF CONCIOUS) UNDER DIRECTIONS OF A PHYSICIAN.

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =============

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

TRANSFER TO A CLOSED CONTAINER.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP FROM FREEZING.

OTHER PRECAUTIONS

NONE

WORK/HYGIENIC PRACTICES

WASH HANDS AFTER USE AND OBSERVE GOOD HYGIENIC PRACTICES.

THIS INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF ACCURATE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS.