

# Silicone Lubricant

## Safety Data Sheet



### SECTION 1: Product and company identification

Product name : Silicone Lubricant  
Use of the substance/mixture : Aerosol Lubricant.  
Product code : 809801  
Company : Share Corporation  
P.O. Box 245013  
Milwaukee, WI 53224  
T (414) 355-4000  
Emergency number : Chemtrec: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Gas 1 H220  
Flam. Aerosol 1 H222  
Liquefied gas H280  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
STOT SE 3 H336  
Asp. Tox. 1 H304

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable gas  
Extremely flammable aerosol  
Contains gas under pressure; may explode if heated  
May be fatal if swallowed and enters airways  
Causes skin irritation  
Causes serious eye irritation  
May cause drowsiness or dizziness

Precautionary statements (GHS-US) :

Keep away from heat, sparks, open flames, hot surfaces, Do not smoke. - No smoking  
Do not spray on an open flame or other ignition source  
Pressurized container: Do not pierce or burn, even after use  
Avoid breathing mist, spray  
Wash thoroughly after handling  
Use only outdoors or in a well-ventilated area  
Wear protective gloves, eye protection  
If swallowed: Immediately call a doctor, a POISON CENTER, Do NOT induce vomiting  
If on skin: Wash with plenty of IF ON SKIN: Wash with plenty of soap and water  
If inhaled: Remove person to fresh air and keep comfortable for breathing  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Call a POISON CENTER, a doctor if you feel unwell  
Specific treatment (see First aid measures on this label)  
Do NOT induce vomiting  
If skin irritation occurs: Get medical advice/attention  
If eye irritation persists: Get medical advice/attention  
Take off contaminated clothing and wash before reuse  
Leaking gas fire: Do not extinguish, unless leak can be stopped safely  
Eliminate all ignition sources if safe to do so  
Store in a well-ventilated place  
Store in a well-ventilated place. Keep container tightly closed  
Store locked up  
Protect from sunlight. Store in a well-ventilated place  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
Dispose of contents/container to comply with local/regional/national/international regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
heptane, n-heptane	(CAS No) 142-82-5	70 - 80	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
propane	(CAS No) 74-98-6	10 - 20	Flam. Gas 1, H220 Compressed gas, H280
butane	(CAS No) 106-97-8	5 - 10	Flam. Gas 1, H220 Compressed gas, H280

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Immediately call a poison center or doctor/physician. Vomiting: prevent asphyxia/aspiration pneumonia.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Extremely flammable. Contents under pressure. May be fatal if swallowed and enters airways. May cause damage to organs (central nervous system) (Inhalation).
Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: May cause respiratory irritation. Headache. Central nervous system depression. May cause drowsiness or dizziness. Unconsciousness. Symptoms of overexposure to vapors include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision and, in extreme cases, death.
Symptoms/injuries after skin contact	: May cause moderate irritation. ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin.
Symptoms/injuries after eye contact	: May cause severe irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable aerosol. Under fire conditions closed containers may rupture or explode.
Explosion hazard	: Contains gas under pressure; may explode if heated. Vapors may travel long distances along ground before igniting/flashing back to vapor source.
Reactivity	: Upon combustion: CO and CO2 are formed.

### 5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment.

# Silicone Lubricant

## Safety Data Sheet



### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Isolate from fire, if possible, without unnecessary risk. Gas is denser than air. May accumulate in low areas e.g. close to the ground.

##### 6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

Emergency procedures : Evacuate unnecessary personnel. NO open flames, NO sparks, and NO smoking.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Isolate area until gas has dispersed. Eliminate every possible source of ignition. Use water spray to disperse the vapors. Collect spillage.

Methods for cleaning up : Take up liquid spill into inert absorbent material.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Do not puncture, incinerate or crush.

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F.

Heat-ignition : KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.

Storage area : Store in a cool area. Store away from heat.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>butane (106-97-8)</b>		
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm
<b>propane (74-98-6)</b>		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
<b>heptane, n-heptane (142-82-5)</b>		
ACGIH	ACGIH TWA (ppm)	400 ppm

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses.



### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Aerosol. clear. mist.

# Silicone Lubricant

## Safety Data Sheet



Odor	: Solvent-like odour
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < 0 °F (liquid portion)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.8 g/ml
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt
Viscosity, dynamic	: No data available
VOC content	: 97 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed.

#### 10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

#### 10.4. Conditions to avoid

No flames, No sparks. Eliminate all sources of ignition. Heat. Welding.

#### 10.5. Incompatible materials

acids. Oxidizing agent.

#### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

# Silicone Lubricant

## Safety Data Sheet



Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: May cause respiratory irritation. Headache. Central nervous system depression. May cause drowsiness or dizziness. Unconsciousness. Symptoms of overexposure to vapors include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision and, in extreme cases, death.
Symptoms/injuries after skin contact	: May cause moderate irritation. ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin.
Symptoms/injuries after eye contact	: May cause severe irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Likely routes of exposure	: Dermal;Inhalation

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

Transport document description	: UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
UN-No.(DOT)	: UN1950
Proper Shipping Name (DOT)	: Aerosols flammable, (each not exceeding 1 L capacity)
Transport hazard class(es) (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	: 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
DOT Special Provisions (49 CFR 172.102)	: N82
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A
DOT Vessel Stowage Other	: 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### Additional information

Other information : No supplementary information available.

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

# Silicone Lubricant

## Safety Data Sheet



This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

butane (106-97-8)
Not listed on SARA Section 313 (Specific toxic chemical listings)
propane (74-98-6)
Not listed on SARA Section 313 (Specific toxic chemical listings)

California Proposition 65 - This product does not contain a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

### SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Liquefied gas	Gases under pressure Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*