

CA

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS AND RELATED MATERIALS



MANUFACTURER: Tru-Test Manufacturing Company
 ADDRESS: (Formerly General Paint & Chemical Co.)
 201 Jandus Road
 Cary, IL 60013

EMERGENCY MEDICAL INFO: 1-800-228-5635
 TECHNICAL INFORMATION: 1-708-639-5383

DATE OF PREPARATION: July 24, 1990

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBERS EZF-Line EZF-1, 2, 7, 8, 11, 12, 14, 15, 16, 17, 49, 0, T & P
 PRODUCT NAME Tru-Test Supreme EZ-Kare Interior Flat Latex Paint
 PRODUCT CLASS Interior Flat Latex Paint

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT / CAS. NO.	WT %	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE
		TLV PPM	PEL	mm Hg @ 20°C
(S) Ethylene Glycol 107-21-1	Less than 5%	50ppm	50ppm	0.1MMHG @ 68°F
Diatomaceous Silica (1) 68855-54-9	Less than 5%	10mg/m ³	0.08mg/m ³	NA

(1) This product only in EZF-2, 12, 14, 15, 16, 17

(S) = This ingredient is subject to the reporting requirements of SEC. 313 SARA Title III
 NA = Not applicable NE = Not established

SECTION III - PHYSICAL DATA

BOILING RANGE 212° F VAPOR DENSITY HEAVIER X LIGHTER THAN AIR
 EVAPORATION RATE ° FASTER X SLOWER THAN ETHER * % VOLATILE VOLUME * WT/GAL
 Volatile Organic Content (VOC) less than 175 gm/L lbs
 *varies with color

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION OSHA Class II FLASH POINT 105°F LEL 0.9
DOT Combustible Liquid

EXTINGUISHING MEDIA:

FOAM ALCOHOL
FOAM CO2 DRY CHEMICAL WATER FOG OTH

UNUSUAL FIRE AND EXPLOSION HAZARDS - Closed containers may explode when exposed to extreme heat. Isolate from heat, sparks and open flame.

SPECIAL FIREFIGHTING PROCEDURES - Treat as a volatile liquid fire. Water spray may be ineffective. If water spray is used, fog nozzles are preferable.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - Severe eye irritation, drying of skin, excessive inhalation, causes headache, dizziness & nausea. Severe eye irritation, drying of skin, excessive inhalation, causes headache, dizziness & nausea. In the Diatomaceous Silica is Crystalline Silica (CS) which is considered a hazard by inhalation, IARC has classified CS as probably carcinogenic for humans (2A), from lab animal studies. CS has not been classified as a MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: carcinogen by NPT or OSHA.

None known to General Paint & Chemical Co

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

EMERGENCY AND FIRST AID PROCEDURES

Eyes & Skin: Wash with fresh water. Wash skin with warm water & soap.

Inhalation: Remove to fresh air. Apply artificial respiration if necessary. Get medical attention.

Ingestion: Do not induce vomiting. Keep person warm and quiet. Get medical attention.

SECTION VI - REACTIVITY DATA

STABILITY UNSTABLE STABLE

HAZARDOUS POLYMERIZATION MAY OCCUR WILL NOT OCCUR
HAZARDOUS DECOMPOSITION PRODUCTS

CONDITIONS TO AVOID Isolate from heat & open fire.

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid contact with strong oxidizing agents

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate all ignition sources. Contain spill, absorb liquid with clay, sand or floor absorbent. Prevent run-off to sewers, streams or other bodies of water.

WASTE DISPOSAL METHOD

Contaminated absorbent may be deposited in a landfill in accordance with local, state and federal regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION - NIOSH/MSHA jointly approved air supplied respirator if TLV limits are exceeded. Approved mechanical filter to remove solid airborne particles of overspray during application.

VENTILATION - Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV.

PROTECTIVE GLOVES - Required to prevent prolonged or repeated contact

EYE PROTECTION - Use of safety eyewear is recommended to prevent eye contact.

OTHER PROTECTIVE EQUIPMENT - Impervious clothing & boots are suggested to prevent prolonged or repeated skin contact.

HYGIENIC PRACTICES:

Wash hands before eating, smoking or using bathroom

Do not reuse contaminated clothing.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat sparks and open flames. For storage conditions see OSHA 1910.106

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact with skin. Containers should be grounded when pouring.

Avoid free fall of more than 2 - 3 inches when pouring.
